

Relay

Striping Color Pack
resurfacer

World's
Thinnest and Most Vibrant
Cementitious Pavement Resurfacer



RELAY™ Striping is a polymer modified cementitious system that is **strong, durable, abrasion-resistant** and able to **withstand all weather conditions**.

It **cures rapidly, is flexible, easy to deploy** and is simply applied with a **brush, roller or spray** at a thickness of under **1mm**.

RELAY™ Striping is a **primerless system** available in a variety of **vibrant colours** for application as a **surface coating** to **protect, repair and beautify** existing pavements, or for use as **pavement safety striping**.



Available Colors

SAFETY STRIPING FOR

PARKING LOTS

ROADS

RUNWAYS

TAXIWAYS

AIRPORTS

SAFETY ZONES

APPLY OVER

ASPHALT

METAL

COATINGS

CONCRETE

WOOD

TEST RECAP

COMPRESSION
(ASTM C-109 MORTAR)
24 HOURS: 6,667 PSI (45 MPA)

SMOKE AND TOXIC FUME EMISSIONS
(BRITISH STANDARD 6853)
ACCEPTED (NEGLECTIBLE EMISSIONS)

ABRASION RESISTANCE
(ASTM C-944)
DEPTH OF WEAR < 0.01 INCHES

FREEZE THAW RESISTANCE
(ASTM C-666)
0% LOSS AFTER 50 CYCLES

SKID TEST
(ASTM E303-93)
GREATER THAN 55 B

BOND STRENGTH
(ASTM C-1583/ACI 503.1R)

WATERPROOF
(ASTM B117-11)
**250 HOURS AND 500 HOURS:
NO RUST OR BLISTERING**

**3 HOUR > 300 PSI
28 DAY > 500 PS**

